

ZESTAWIENIE STALI KONSTRUKCYJNEJ

KONSTRUKCJA DACHU

Item Nr.	Term	Supply Kg	Supply unit
A	L-PROFILE L 76/180 x6 / , L= 90, W= 245, T= 6.00	80	80
A	L-PROFILE L 80/80 x5 / , L= 90, W= 150, T= 5.00	2	4
A	Capping beam H 42/119/110/119/42 x4 / , L= 7170, W= 400, T= 4.00	1 081	12
A	Capping Beam H 42/119/110/119/42 x4 / , L= 8930, W= 400, T= 4.00	449	4
A	Capping Beam H 42/119/110/119/42 x4 / , L= 8953, W= 400, T= 4.00	450	4
A	JOINT IN CRESTBEAM H 37/119/120/119/37 x4 / , L= 120, W= 400, T= 4.00	6	4
A	JOINT IN CRESTBEAM H 37/119/120/119/37 x4 / , L= 460, W= 400, T= 4.00	139	24
A	Capping Beam H 41/118/108/118/41 x3 / , L= 7190, W= 400, T= 3.00	406	6
A	Capping Beam H 41/118/108/118/41 x3 / , L= 8946, W= 400, T= 3.00	169	2
A	Capping Beam H 41/118/108/118/41 x3 / , L= 8958, W= 400, T= 3.00	169	2
A	C-Profile C 34/94/170/94/34 x3 / , L= 6688, W= 400, T= 3.00	504	8
A	C-Profile C 34/94/170/94/34 x3 / , L= 6988, W= 400, T= 3.00	790	12
A	BRACE TYPE D PL 42/1669 x4 / , L= 1669, W= 42, T= 4.00	9	4
A	BRACE TYPE D DIVIDED IN 4 PARTS / , L= 2022, W= 200, T= 4.00	13	4
A	BRACE TYPE D PL 42/2155 x4 / , L= 2155, W= 42, T= 4.00	11	4
A	BRACE TYPE D PL 42/2280 x4 / , L= 2280, W= 42, T= 4.00	12	4
A	BRACE TYPE D PL 42/2855 x4 / , L= 2855, W= 42, T= 4.00	30	8
A	BRACE TYPE E DIVIDED IN 4 PARTS / , L= 3000, W= 200, T= 4.00	56	12
A	Z-250 Z 20/60/250/60/20 x2 / , L= 8325, W= 400, T= 2.00	314	6
A	Stretching screw M16 (for M12 screw) CE M16 /	14	12
A	Screw Hex cap 8.8 FZV Llentab + Nut M12x37 (3-16) + M12 /	41	680
A	Washer FZV 13x24x8 /	12	680

A	PLATE 462x2495x1.25	294	64
	HPR T130 / L=9713, T=0.7	3 376	44
	HPR T130 / L=7950, T=0.7	8 290	132
	HPR T130 / L=9001, T=0.7	3 129	44
	HPR T130 / L=2163, T=0.7	137	8
	HPR T130 / L=5101, T=0.7	322	8

Delivery Weight 20 303

Unit

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS