

# **ZESTAWIENIE STALI KONSTRUKCYJNEJ**

## **ŚCIANY PODŁUŻNE**

<b>Item Nr.</b>	<b>Term</b>	<b>Supply Kg</b>	<b>Supply unit</b>
A	GATE FRAME C 34/96/170/96/34 x4 / , L= 3993, W= 400, T= 4.00	100	2
A	Gate Frame C 34/96/170/96/34 x4 / , L= 8343, W= 400, T= 4.00	419	4
A	Door Frame C 34/96/170/96/34 x4 / , L= 2241, W= 400, T= 4.00	56	2
A	Gate Frame C 34/96/170/96/34 x4 / , L= 6779, W= 400, T= 4.00	170	2
A	BRACE TYPE D PL 42/2412 x4 / , L= 2412, W= 42, T= 4.00	50	16
A	BRACE TYPE D PL 42/2573 x4 / , L= 2573, W= 42, T= 4.00	54	16
A	BRACE TYPE D PL 42/2855 x4 / , L= 2855, W= 42, T= 4.00	119	32
A	BRACE TYPE E DIVIDED IN 4 PARTS / , L= 3000, W= 200, T= 4.00	301	64
A	CONNECTION PROFILE DOOR IN PANELL C 28/82/100/82/28 x4 / , L= 2200, W= 290, T= 4.00	80	4
A	Stretching screw M16 (for M12 screw) CE M16 /	38	32
A	Screw Hex cap 8.8 FZV Llentab + Nut M12x37 (3-16) + M12 /	34	552
A	Screw MFT Zinc M12x35 + Nut (Countersunk head) M12x35 (T50) + M12Nut /		16
A	Washer FZV 13x24x8 /	10	572
A	Connection profile L 94/115 x5 / , L= 190, W= 245, T= 5.00	11	6
A	Conn.profile Reinf. Frame L 113/113 x3 / , L= 70, W= 220, T= 3.00	3	8
A	Stud Anchor HSA-F M12x100 /	2	8
A	Conn. profile Gateframe L 156/76 x4 / , L= 224, W= 67, T= 4.00	13	28

**Delivery Weight 1 460**

**Unit**

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS