

# **ZESTAWIENIE STALI KONSTRUKCYJNEJ**

## **KONSTRUKCJA ŚCIAN SZCZYTOWYCH**

<b>Item Nr.</b>	<b>Term</b>	<b>Supply Kg</b>	<b>Supply unit</b>
A	Conn. Truss-Column C 40/129/100/129/40 x5 / , L= 415, W= 400, T= 5.00	26	4
A	GATE FRAME C 34/96/170/96/34 x4 / , L= 2993, W= 400, T= 4.00	38	1
A	Gate Frame C 34/96/170/96/34 x4 / , L= 9600, W= 400, T= 4.00	241	2
A	Door Frame C 34/96/170/96/34 x4 / , L= 5579, W= 400, T= 4.00	140	2
A	Gate Frame C 34/96/170/96/34 x4 / , L= 6179, W= 400, T= 4.00	78	1
A	Gable Pillar C 45/125/300/125/45 x5 / , L= 9410, W= 600, T= 5.00	443	2
A	Gable Pillar C 45/125/300/125/45 x5 / , L= 9447, W= 600, T= 5.00	1 335	6
A	Gable Pillar C 45/125/300/125/45 x5 / , L= 9803, W= 600, T= 5.00	1 847	8
A	Gable Pillar C 45/125/300/125/45 x5 / , L= 9192, W= 600, T= 5.00	1 732	8
A	Gable Beam C 34/94/170/94/34 x3 / , L= 1190, W= 400, T= 3.00	45	4
A	Gable Beam C 34/94/170/94/34 x3 / , L= 3356, W= 400, T= 3.00	126	4
A	Conn. Profile C 34/94/170/94/34 x3 / , L= 360, W= 400, T= 3.00	7	2
A	Gate Frame C 34/94/170/94/34 x3 / , L= 3773, W= 400, T= 3.00	36	1
A	PILLAR-CONNECTION U 58/100/58 x4 / , L= 200, W= 200, T= 4.00	121	96
A	U-Profile U 60/94/60 x4 / , L= 228, W= 200, T= 4.00	1	1
A	Distance plate standard pillar PL 200/200x4 / , L= 200, W= 200, T= 4.00	121	96
A	U-PROFILE SEE SCHABLON DRAWING / , L= 2500, W= 220, T= 3.00	260	20
A	Z-Profile GABLEPILLAR CONN.PROFILE C300 SEE SCHABLON DRAWING / , L= 1495, W= 220, T= 3.00	31	4
A	Z-Profile GABLEPILLAR CONN.PROFILE C300 SEE SCHABLON DRAWING / , L= 2495, W= 220, T= 3.00	155	12
A	Gate Frame C 19/77/100/77/19 x3 / , L= 4143, W= 268, T= 3.00	26	1
A	Column C 45/135/170/135/45 x5 / , L= 9613, W= 490, T= 5.00	185	1

A	CONNECTION PROFILE DOOR IN PANELL C 28/82/100/82/28 x4 / , L= 2200, W= 290, T= 4.00	80	4
A	Screw Hex cap 8.8 FZV Llentab + Nut M12x37 (3-16) + M12 /	57	932
A	Screw Hex cap 8.8 FZV Llentab + Nut M12x45 (15-25) + M12 /	3	48
A	M10 clamp M10 / , L= 160, T= 10.00		32
A	Gable pillar foot (M16 Stud anchor) L 98/130 x5 / , L= 220, W= 245, T= 5.00	2	1
A	Distance plate Gable pillar PL 122x145 / , L= 245, W= 123, T= 5.00	2	2
A	DISTANCE PLATE C-250D for M20 PL 290/272 x4 / , L= 272, W= 290, T= 4.00	59	24
A	Pillar foot "250" 4xM20 for braces 250 M20 / , L= 240, W= 300	185	12
A	Washer FZV 13x24x8 /	17	980
A	Connection profile L 94/115 x5 / , L= 190, W= 245, T= 5.00	11	6
A	Conn.profile Reinf. Frame L 113/113 x3 / , L= 70, W= 220, T= 3.00	3	8
A	Conn. profile Gateframe L 156/76 x4 / , L= 224, W= 67, T= 4.00	4	9
A	Nut hex 8 FZV M10 /		64
A	Washer FZV 10.5x22x2 /	0	64

**Delivery Weight 7 417**

**Unit**

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS